


NEPTUNE 10 SUCTION & DELIVERY

10 BAR WATER SUCTION & DELIVERY



Order Ref: WSH-SIZE MM



Tube: Natural and synthetic rubber.

Reinforcement: High tensile synthetic textile and steel helix wire.

Cover: Abrasion and weather resistant synthetic rubber.

Application: Water suction and discharge in industrial and construction services.

INTERNAL DIAMETER		OUTER DIAMETER	WORKING PRESSURE		BURSTING PRESSURE		VACUUM	BEND RADIUS	HOSE WEIGHT	COIL LENGTH
inch	mm	mm	BAR	PSI	BAR	PSI	m.H ² O	mm	gr/m	m
1	25	35	10	145	30	435	-0.92	95	673	30
1 1/4	32	42	10	145	30	435	-0.92	125	881	30
-	35	45	10	145	30	435	-0.92	135	967	30
1 1/2	38	48	10	145	30	435	-0.92	150	1119	30/40
2	51	62	10	145	30	435	-0.92	215	1684	20/30/40
-	60	71	10	145	30	435	-0.92	250	1856	6 / 30
2 1/2	64	75	10	145	30	435	-0.92	280	2129	6 / 30
3	76	88	10	145	30	435	-0.92	350	2698	6/30
-	80	95	10	145	30	435	-0.92	400	2950	40
4	102	115	10	145	30	435	-0.92	490	3825	6/30
5	127	144	10	145	30	435	-0.92	650	5998	30
6	152	170	10	116	30	348	-0.92	800	7600	3 / 6 / 30
8	203	222	10	145	30	435	-0.92	1120	12220	3 / 6 / 30
10	254	279	10	145	30	435	-0.92	1525	18450	3
12	305	329	10	145	30	435	-0.92	1950	24040	3