



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

1. DESCRIPTION

The Viking model DRV-1 dry valve is a latching differential valve used to separate the water supply from the dry pipe sprinkler system.

The valve head provides a positive mechanical seal within the valve, separating the supply water pressure from the air in the system. The differential design allows a low system air pressure to control a higher water supply pressure. When the air pressure in the dry pipe system is lowered sufficiently to destroy the pressure differential - due to a sprinkler activation and subsequent loss of air pressure in the piping - the valve opens allowing water to enter the dry pipe system.

The valve is also designed to operate a water motor alarm and/or an electric pressure alarm switch.

The Viking model D-2 accelerator can be used to speed up the operation of the valve on large capacity systems or where faster action is required.

Features:

- Lightweight design
- Small footprint
- Low pressure loss
- Easy trim design
- Alarm trim options available to suit local market demands
- Fast assembly on site or available pre-assembled
- BVG-1 butterfly valve pre-mounted to the main valve (Norwegian market only)




Fig 1.1 - DRV-1 with pressure switch
(Image for illustration purposes only)

2. LISTINGS AND APPROVALS



cULus: Category VPZV.EX27884



FM: Class 1020



EN 12259-3:2000 LPCB Cert ref. 096x

3. TECHNICAL INFORMATION

3.1 Valve data

Table 3.1.1. - Valve specifications	
Maximum working pressure:	17.2 bar (250 psi)
Minimum operating pressure:	1.4 bar (20 psi)
Operating temperature:	4 °C to 60 °C (39 °F to 140 °F)
Style:	Straight through
Sizes:	3" / DN80, 4" / DN100 & 6" / DN150
Connections:	Grooved-Grooved
Differential:	1:5
Colour:	Red
Materials:	Housing: Ductile iron Seat/Disk: Brass Gaskets: Nitrile rubber

For further detailed technical information, refer to the DRV-1 Operating Instructions (part number 927081, Doc.ID 100097582), available on www.viking-emea.com



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

3.2 Trim options


The DRV-1 is available with or without the model D-2 accelerator. Further options are available to meet the needs of local markets and also to provide monitoring of the dry valve.

3.2.1 DRV-1 without accelerator

The model DRV-1 is supplied with all the base trim necessary for the valve to operate. The valves are provided with the trim pre-mounted onto the valve as standard but the trim can be provided separately if required.

The trim also includes a system drain.

An alarm line option (**see section 3.2.3**) is required to successfully signal an alarm.




3.2.2 DRV-1 without accelerator (Norwegian market)


The DRV-1 base trim comes with air pressure monitoring kit specially designed for the Norwegian market. The base trim and the BVG-1 butterfly valve are both pre-mounted to the main valve.

The trim also includes a system drain.


The Norway alarm line option (**see section 3.2.3.6**) is required to successfully signal an alarm. The alarm line is not supplied pre-mounted.



Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com



**Fig. 3.2.3.a - DRV-1
with accelerator**




**Fig. 3.2.3.c - DRV-1
with accelerator
(Swedish market)**

3.2.3 DRV-1 with accelerator

The model DRV-1 with accelerator trim adds the model D-2 accelerator and associated trim. The addition of an accelerator increases the sensitivity of the dry valve assembly by reacting to a smaller drop in system air pressure. This speeds up the operation of the dry system and allows for system designers to increase the size of dry systems.

The accelerator trim for the Swedish market comes with the ball valve monitoring switches installed.

An alarm line option (*see section 3.2.3*) is required to successfully signal an alarm.



**Fig. 3.2.3.b - DRV-1
with accelerator
(Norwegian market)**




TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Nieder Korn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com


3.2.3 Alarm Trim

The DRV-1 is available with seven alarm trim options to suit local requirements. Each alarm trim option includes the required number of alarm pressure switches and, where required, alarm shut off valves and monitoring.




3.2.3.1 Standard

The standard alarm option includes a single alarm pressure switch, alarm shut-off valve and connection for the water motor alarm.




3.2.3.2 UK

The UK alarm trim option includes an alarm pressure switch (without interruption), plus a connection to the water motor alarm with alarm shut-off valve.



3.2.3.3 France

The France alarm trim option includes an alarm pressure switch (without interruption), plus a connection to the water motor alarm with alarm shut-off valve.



3.2.3.4 Germany & Finland


The Germany & Finland alarm option includes a single alarm pressure switch, monitored alarm shut-off valve and connection for the water motor alarm.



TECHNICAL DATA


DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com




3.2.3.5 Netherlands

The Netherlands alarm option includes a single alarm pressure switch and a connection to the water motor alarm without alarm shut-off valve.



3.2.3.6 Norway

The Norway alarm option includes dual alarm pressure switches each with monitored shut-off valves.



3.2.3.7 Sweden

The Sweden alarm option includes a single alarm pressure switch, alarm pressure gauge, monitored alarm shut-off valve and connection for the water motor alarm.

3.2.4 Monitoring Kit

To monitor the air pressure in the dry system pipework, the monitoring kit can be added to the trim. The kit includes the air supervisory pressure switch as well as the necessary nipples and fittings to connect them to the trim. The kit is not assembled onto the trim.

3.2.5 Air Supervisory Pressure Switch

The air supervisory switch is also available as a separate component without the pressure gauge.



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

3.2.6 Air Supply Kit

The air supply kit should be connected to the incoming air supply on each DRV-1 valve. The kit includes an orifice which limits the flow of air into the system which prevents excessive trip times on system operation.

The kit includes a normally-closed bypass valve to allow faster fill times on system commissioning.

The air supply kit can be provided with a pressure relief valve pre-set depending on the incoming water supply pressure. The pressure relief valve must be ordered separately.

Table 3.2.6.1 - Pressure relief valve for air supply kit

Set-point (bar)	Suitable for water supply pressures (bar)	Pressure relief valve - Part number
3.5	Up to 10	131054
3.9	10.1 to 12	849833
4.3	12.1 to 14	849834
4.4	14.1 to 16	849835

4. ORDERING INFORMATION

To order your fully assembled DRV-1 dry valve, follow our selection process steps:

Step 1 – Select the valve size and type (required)

Step 2 – Add the alarm option (required)

Step 3 – Select the options required (optional)

The DRV-1 is also available with the trim unassembled. Select the valve and base trim from the table below.

The accelerator and trim can be added using the part from the table above.

Table 4.1 - Ordering information - assemblies

Step	Part	Size / Type	Groove-Groove	Groove-Groove with Accelerator ¹
1	Valve & base trim	3" / DN80	A/DRV1-3GG	A/DRV1-3GG-A
		4" / DN100	A/DRV1-4GG	A/DRV1-4GG-A
		6" / DN150 (165 mm)	A/DRV1-6GG165	A/DRV1-6GG165-A
		6" / DN150 (168 mm)	A/DRV1-6GG168	A/DRV1-6GG168-A
	Valve with base trim and BVG-1 (Norwegian market only)	3" / DN80	A/DRV1-3GG-N	A/DRV1-3GG-AN
		4" / DN100	A/DRV1-4GG-N	A/DRV1-4GG-AN
		6" / DN150 (168 mm)	A/DRV1-6GG168-N	A/DRV1-6GG168-AN
	Valve with base trim (Swedish market only)	3" / DN80	A/DRV1-3GG	A/DRV1-3GG-A-SW
		4" / DN100	A/DRV1-4GG	A/DRV1-3GG-A-SW
		6" / DN150 (168 mm)	A/DRV1-6GG168	A/DRV1-6GG168-A-SW
2	Alarm	Standard		19420
		UK		19416
		France		19418
		Germany & Finland		19417
		Netherlands		19421
		Norway	Included in item #1 above	
		Sweden		19419
3	Options	Accelerator & trim	DRV1-AK	
		Monitoring kit	DRV1-MK	
		Air supervisory switch	PS401A (1 contact), PS402A (2 contacts)	
		Air supply kit	DRV1-AS	
		Pressure relief valve for air supply kit	see table 3.2.6.1	

¹ already includes option "Accelerator & trim"



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

Table 4.2 - Ordering information - individual parts

Loose Trim	3" / DN80	DRV1-T3
	4" / DN100	DRV1-T4
	6" / DN150	DRV1-T6
Valve Only	3" / DN80	DRV1-3GG
	4" / DN100	DRV1-4GG
	6" / DN150 (165 mm)	DRV1-6GG165
	6" / DN150 (168 mm)	DRV1-6GG168

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
 Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5. DIMENSIONS

5.1 Valve plus operating trim (no accelerator)




Fig 5.1.1 - Front view




Fig 5.1.2 - Side view




Fig 5.1.3 - Plan view

Table 5.1.4 - Dimensions (mm) & weight (kg)			
	3" / DN80	4" / DN100	6" / DN150
A1	146	161	191
A2	197	197	197
A3	339	357	355
B1	192	208	226
B2	164	174	194
C1	139	154	184
C2	340	340	340
C3	188	206	204
D1	111	121	141
D2	116	116	116
D3	180	198	198
E1	125	135	153
E2	125	135	153
E3	70	94	97
H1	398	416	408
H2	295	330	345
T1	153	177	195
T2	360	360	360
Weight	23	26	35



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5.2 Valve plus operating trim and accelerator




Fig 5.2.1 - Front view




Fig 5.2.2 - Plan view

Table 5.2.3 - Dimensions (mm) & weight (kg)			
	3" / DN80	4" / DN100	6" / DN150
B3	251	266	296
F1	202	217	247
F2	229	229	229
F3	339	357	354
H4	711	729	724
Weight	29	32	41



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5.3 Valve plus operating trim and monitoring kit (no accelerator)




Fig 5.3.1 - Front view

Table 5.3.2 - Dimensions (mm) & weight (kg)			
	3" / DN80	4" / DN100	6" / DN150
H3	456	474	496
Weight	24	27	36



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5.4 Valve plus operating trim and alarm line options (no accelerator)




Fig 5.4.1 - Front view (standard trim shown)

Table 5.4.2 - Dimensions (mm) & weight (kg)				
		3" / DN80	4" / DN100	6" / DN150
Standard	H3	650	650	650
	Weight	25	28	37
UK	H3	420	420	420
	Weight	25	28	37
France	H3	450	450	450
	Weight	25	28	37
Germany	H3	550	550	550
	Weight	25	28	37
Netherlands	H3	450	450	450
	Weight	24	27	36
Norway	H3	660	660	660
	Weight	27	30	39
Sweden & Finland	H3	590	590	590
	Weight	26	29	38



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5.5 Valve plus operating trim and monitoring kit (no accelerator)




Fig 5.5.1 - Front view




Fig 5.5.2 - Side view




Fig 5.5.3 - Top view

Table 5.5.4 - Dimensions (mm) & weight (kg)

	3" / DN80	4" / DN100	6" / DN150
A1	146	161	191
A2	197	197	197
A3	436	473	503
B1	355	370	400
B2	164	174	194
D1	111	121	141
D2	116	116	116
D3	277	314	346
E1	125	135	153
E2	125	135	153
H1	712	740	803
H2	392	446	493
T1	232	253	296
T2	402	402	402
Weight	39.14	43.59	59.76



TECHNICAL DATA

DRV-1 DRY ALARM VALVE 3" (DN80) – 6" (DN150)

Viking S.A., Zone Industrielle Haneboesch, L-4562 Differdange/Niederkorn, Luxembourg
Tel.: +352-58-37-37-1 Fax: +352-58-37-36 Email: vikinglux@viking-emea.com Web: www.viking-emea.com

5.6 Norwegian version - valve with operating trim, accelerator, alarm line and pre-mounted butterfly valve




Table 5.6.1 - Dimensions (mm) & weight (kg)

	3" / DN80	4" / DN100	6" / DN150
H4	986	1013	1076
Weight	45.14	49.93	65.76

6. AVAILABILITY

Please contact your local Viking sales office for further information.
The product is available directly from Viking and official distributors only.

EMEA: Viking S.A., Z.I. Haneboesch, L-4562 Differdange/Niederkorn, Tel.: +352 58 37 37 -1, Fax: +352 58 37 36,
vikinglux@viking-emea.com